



TECHNICAL SPECIFICATIONS

TEFLON HOSES (PTFE)



Resistance Compatible with any brake fluid, clutch fluids, fuel (E85), Alcohol, Hydraulics
Minimum Temperature - 70°C
Maximum Temperature 250°C

Part No.	Size (AN)	Inner (mm)	Outer (mm)	Operating Pressure (PSI/BAR)	Burst Pressure (PSI/BAR)	Outer sheath
QGSS-PT-03	3	3,56	6,35	4000 / 275	12000 / 827	Stainless Steel
QGSS-PT-03BLK	3	3,56	7,40	4000 / 275	12000 / 827	Coating
QGSS-PT-03CLR	3	3,56	7,40	4000 / 275	12000 / 827	Coating
QGSS-PT-LW-03-BLK	3	3,56	6,35	4000 / 275	12000 / 827	Nylon
QGSS-PT-04	4	4,83	8,00	4000 / 275	12000 / 827	Stainless Steel
QGSS-PT-04BLK	4	4,83	8,90	4000 / 275	12000 / 827	Coating
QGSS-PT-04CLR	4	4,83	8,90	4000 / 275	12000 / 827	Coating
QGSS-PT-LW-04-BLK	4	4,83	8,00	4000 / 275	12000 / 827	Nylon
QGSS-PT-06	6	8,13	10,92	3000 / 207	10000 / 690	Stainless Steel
QGSS-PT-06BLK	6	8,13	12,40	3000 / 207	10000 / 690	Coating
QGSS-PT-06CLR	6	8,13	12,40	3000 / 207	10000 / 690	Coating
QGSS-PT-LW-06-BLK	6	8,13	10,92	3000 / 207	10000 / 690	Nylon
QGSS-PT-08	8	10,67	13,72	2500 / 172	8000 / 550	Stainless Steel
QGSS-PT-08BLK	8	10,67	15,50	2500 / 172	8000 / 550	Coating
QGSS-PT-08CLR	8	10,67	15,50	2500 / 172	8000 / 550	Coating
QGSS-PT-LW-08-BLK	8	10,67	13,72	2500 / 172	8000 / 550	Nylon
QGSS-PT-10	10	12,95	16,00	2000 / 138	6000 / 413	Stainless Steel

QSP PRODUCTS

SCHUTWEG 25 - 5145NP - WAALWIJK - THE NETHERLANDS
WWW.QSPPRODUCTS.NL